

Photonic Doppler velocimetry probe used to measure grain boundaries of dynamic shocked materials

Robert M. Malone, Daniel K. Frayer, Morris I. Kaufman, Kevin D. McGillivray, Vincent T. Romero


Mission Support and Test Services, LLC

New Mexico Operations



Las Vegas Operations

Steven A. Clarke, Saryu J. Fensin, David R. Jones

Los Alamos National Laboratory




This work was done by National Security Technologies, LLC, under Contract No. DE-AC52-06NA25946 with the U.S. Department of Energy.



Gas gun fires projectile from right to left. Projectile enters into catch tank where it hits the target material. Target undergoes shock compressions.




Photon Doppler Velocimetry (PDV)




Simplified schematic diagram of PDV showing the unshifted (reference) light in red, the Doppler shifted light reflecting off the moving surface in blue, and the combined unshifted plus shifted light in green.


Spectrogram of eight PDV data records, recorded on a single digitizer




This metal underwent a double shock producing ejecta traveling faster than the moving surface.





Fiber Channel Organization






NSTec Los Alamos Operations
Brian Cox, Vince Romero
"AOC Fisheye Backlit"
Feb 6, 2012

Improved fisheye PDV probe design. Turning mirrors have been eliminated.




PDV probe with Stereo Imaging




PDV fiber arrays are index matched to first fused silica lens


Bugeye probe could be used for stereo PDV and stereo imaging



PDV Details

Ceramic mask for fiber arrays
(Photoveel II)
8 mm diameter,
1.5 mm thick,
126 μm tapered holes







Metrology

Reflected label
off prism facet



90° azimuth

Future probe designs are for understanding how grain boundaries are affected by shocks



Gas Gun PDV microscope


37 fiber 2D PROFA fiber array
10 μm core
37 μm core spacing



Schott Coherent Bundle
0.9 mm active diameter
7.4 μm pixel size
18,000 pixels
121 resolution elements across the diameter,
Imaging designed for 800-900 nm wavelength band


Gas Gun PDV microscope

37 fiber 2D PROFA fiber array
10 μm core
37 μm core spacing




Schott Coherent Bundle
0.9 mm active diameter
7.4 μm pixel size
18,000 pixels
121 resolution elements across the diameter,
Imaging designed for 800-900 nm wavelength band


Four 19-fiber PROFA arrays on same wafer as 189 individual 125 μm PDV fibers
(12-channel MT ribbon connectors are used)




Two 19-fiber PROFA arrays on same wafer as 189 individual 125 μm PDV fibers
(not all PROFAs and not all PDV channels are shown)




37 fiber 2D PROFA fiber array
10 μm core
37 μm core spacing
MTP connectorized into 12-fiber ribbons
\$2,620





Another option:
61 fiber 2D PROFA fiber array (not shown)
10 μm core
37 μm core spacing
MTP connectorized into 12-fiber ribbons
\$3,720




Chiral Photonics,
61 fiber 2D PROFA fiber array,
10 μm core,
37 μm core spacing,
FC/APC connectors,
\$5,865






Measuring dB loss at PROFA array interface to Fused Silica lens, while glue is setting.

Gas Gun PDV microscope




61 fiber 2D PROFA fiber array,
10 μm core,
37 μm core spacing,
FC/APC connectors,
\$5,865

PROFA array pattern for 61 fibers



Pitch 37 μm
Average error in spacing 0.5 μm
Maximum error in spacing 1.8 μm



SCHOTT Leached Image Bundles

Flexible Imaging Applications




\$875 per individual image bundle,
\$845 each when ordering 10 quantity.

OD Outer Diameter (mm)	Length (mm)	Quality Area Diameter (mm)	Pixel Size (μ)	Pixel Count (k)	Distal Ferrule Diameter (mm)	Proximal Ferrule Diameter (mm)
1.05	760	0.9	7.4	18	1.22 x 5.60	1.22 x 12.80


SCHOTT
1534321
RLIB CVET, 1.05 X 760, 7.6M, 18K (19pc)
SN: 30-651
QC: LC DATE: 12/6/17

Scan of folded photo
(should be no crease)





Imaging system tilted at 18°


Gas Gun PDV microscope




Optomechanical design: monolithic approach




Monolithic design: customer concerns



IR microscope can be set to different magnifications



10 μm spot size from PDV fiber probe, seen at 1550 nm on the IR microscope



In this photo, the intensity of PDV spot is saturating camera. So, some spot size blooming occurs.

37 fiber 2D PROFA fiber array
10 μm core
37 μm core spacing
MTP connectorized into 12-fiber ribbons
\$2,620

BK7 window,
3" diameter,
1/4" thick

8.0 mm diameter field of view

6.6"

40X magnification

50 mm f/3.8 lens

Needs 100 mm EFL macro lens

2 mm diameter coherent bundle

